IL-TOP-1831是一款直行程气动阀门定位器，可安装到各种气动阀门上，如不锈钢气动蝶阀、隔膜阀、角座阀、截止阀、调节阀、球阀、换向阀等。安装有该定位器后，可实现阀门流量调节，自动化控制、阀门位置显示，该产品具有外观佳、体积小、安装简单方便、无需专业人员即可操作调试。

IL-TOP-1831 is pneumatic valve positioner which is used for linear motion. It could be installed to various kinds of pneumatic valve, such as pneumatic butterfly valve, diaphragm valve, angle seat valve, globe valve, regulating valve, ball valve, reversing valve etc. which is with stainless steel pneumatic actuator. With the positioner, could regulate valve flow, control automatically, show valve position.This positioner are with good appearance, small volume, easy installation, could be operated and debugged without professional.

功能描述/货号 Functional description/Item No.	IL-TOP-阀门定位器-功能选择-货物代码 IL-TOP-Valve Positioner-Function Selection-Cargo Code Item No.								
	183131	183132	183131-P	183132-P	183231	183232	183231-P	183232-P	备注说明 Remark
价格(含税) RMB price	3580	4280	4000	4700	3580	4280	4000	4700	
输入(INPUT): 0/4-20mA/0-5V/10V	No	No	yes	yes	No	No	yes	yes	外部信号输入 External signal input
输入(INPUT): 0/4-20mA	yes	yes	yes	yes	yes	yes	yes	yes	
输出(Output): 0/4-20mA/0-5V/10V	No	No	yes	yes	No	No	yes	yes	反馈输出 Feedback output
单作用 Single action	yes	No	yes	No	yes	No	yes	No	气动执行器 Pneumatic actuator
双作用 Double-acting	No	yes	No	yes	No	yes	No	yes	
供电 Power supply: DC24V ± 10%	yes	yes	yes	yes	yes	yes	yes	yes	电源 Power supply
总线通讯 Bus communication: MODE BUS RS485	yes	yes	No	No	yes	yes	No	No	总线通讯 Bus communication
适用范围 Range of application: ≤114气缸 Cylinder	yes	yes	yes	yes	No	No	No	No	≤114 气缸Clylinder, 容量Capacity: ≥ 50& ≤220ml
适用范围 Range of application: ≥ 133气缸 Cylinder	No	No	No	No	yes	yes	yes	yes	≥Φ133 气缸Clylinder, 容量Capacity: ≥ 200 & ≤1000ml
故障，断气、断电，复位(推荐) Cut off air source, power supply, valve position automatic reset (recommend)	yes	yes	yes	yes	yes	yes	yes	yes	故障时阀位复位 Valve position reset in case of failure

功能描述/货号 Functional description/Item No.	IL-TOP-阀门定位器-功能选择-货物代码 IL-TOP-Valve Positioner-Function Selection-Cargo Code Item No.								
	183131-1	183132-1	183131-1-P	183132-1-P	183231-1	183232-1	183231-1-P	183232-1-P	备注说明 Remark
价格(含税) RMB price	3880	4580	4300	5000	3880	4580	4300	5000	
输入(INPUT): 0/4-20mA/0-5V/10V	No	No	yes	yes	No	No	yes	yes	外部信号输入 External signal input
输入(INPUT): 0/4-20mA	yes	yes	yes	yes	yes	yes	yes	yes	
输出(Output): 0/4-20mA/0-5V/10V	No	No	yes	yes	No	No	yes	yes	反馈输出 Feedback output
单作用 Single action	yes	No	yes	No	yes	No	yes	No	气动执行器 Pneumatic actuator
双作用 Double-acting	No	yes	No	yes	No	yes	No	yes	
供电 power supply: DC24V ± 10%	yes	yes	yes	yes	yes	yes	yes	yes	电源 Power supply
总线通讯 Bus communication: MODE BUS RS485	yes	yes	No	No	yes	yes	No	No	总线通讯 Bus communication
适用范围 Scope of application: ≤114气缸 Cylinder	yes	yes	yes	yes	No	No	No	No	≤114 气缸Clylinder, 容量Capacity: ≥ 50& ≤220ml
适用范围 Scope of application: ≥ 133气缸 Cylinder	No	No	No	No	yes	yes	yes	yes	≥Φ133 气缸Clylinder, 容量Capacity≥ 200 & ≤1000ml
故障，断气、断电，阀位保持 Fault, cut off air source, outage, keep valve position	yes	yes	yes	yes	yes	yes	yes	yes	故障时阀位保持 Keep valve position in Case of failure

注意：订货时请注意货号，例如“183131”；” yes “表示含该功能；” No “表示未含该功能
Note: Please pay attention to item number when placing order, for example of "183131": "yes" means it has the function, "No" means it does not contain the function