DJ-JZ1 系列乳化均质泵
DJ-JZ1 series emulsifying homogenizing pump



移动式+控制箱+料斗
Mobile+control box+hopper



移动式+控制箱+均质泵
Mobile+control box+homogenizing pump



移动式均质泵
Mobile homogenizing pump



移动式均质泵+R型三通接口
Mobile homogenizer pump+R-type tee inlet

DJ-JZ 系列多级乳化均质泵
DJ-JZ series multi-stage emulsifying homogenizing pump



高效分散、剪切、细化、破碎、
乳化、混合、均质、高洁净的解决方案
High-efficiency dispersion, cut, refinement, smash, emulsification, mixing, homogenization, high purity solution

非常简单的维护、
无需专用工具、专业人员
Very simple maintenance, no special tools required, no professionals required

技术参数 Technical Specifications

最大流量 Max flow	50m³/h
最大功率 Max power	160KW
最高温度 Max temperature	-20℃到140℃
材质 Material	304 /316L, 1.431/1.4404, ASME BPE 316L, 1.4435 NB2 Fe≤0.5%　双相钢 Dual-phase steel 2205，哈氏合金 Hastelloy alloy C276
表面处理 Surface treatment	≤ Ra0.8μm，≤ Ra0.6μm，≤ Ra0.4μm
机封 Mechanical seal	单机封和双机封 Single and double mechanical seals
机封组合 Mechanical seal combination	详见配置表 See configuration table
进/出口连接 Inlet/outlet connection	螺纹、卡箍、法兰、无菌法兰 Thread, clamp, flange, Aseptic flange
认证 Certification	3-A-02-12(N.O.1579); MD/06/42-EC (N.O.70521616101-00); FDA 177.2600; USP CLASS-II; EG/VO1935/2004