仪表
Meter

流量变送器系列
Flow transmitter series



●材质：304/1.4301，316L/1.4404
●流量：根据用户定义
●温度：-30℃~150℃ (根据用户定义)
●模拟量输出：4-20mA，0-5V，0-10V
●开关量输出：PNP NPN
●压力：10bar(适用于真空环境)
●供电：DC 24V
●防护：IP65/IP69
●防爆：1. 本安防爆等级Ex ia II Bt4；2.隔爆等级 EXD II BT4

●Material: 304/1.4301, 316L/1.4404
●Flow: According to user definition
●Temperature: -30℃~150℃ (according to user definition)
●Analog output: 4-20mA, 0-5V, 0-10V
●Switch output: PNP NPN
●Pressure: 10bar (suitable for vacuum environment)
●Power supply: DC 24V
●Protection: IP65/IP69
●Explosion-proof: 1.Intrinsically-safe explosion-proof Ex ia II BT4. 2.EXD II BT4

传感器系列
Sensor series


音叉物位传感器
Tuning fork level sensor


防爆电感传感器
Explosion-proof inductive sensor


电感传感器
Inductive sensor


航插电感传感器
Aviation plug inductance sensor

音叉物位传感器 Tuning fork level sensor

●环境温度：80℃
●模拟量输出：4-20mA，0-5V，0-10V
●开关量输出：PNP NPN
●供电：DC 24V　AC220V/110V
●防护：IP65/IP69

●Environmental temperature: 80℃
●Analog output: 4-20mA, 0-5V, 0-10V
●Switch output: PNP NPN
●Power supply: DC 24V AC220V/110V
●Protection: IP65/IP69

震动器系列
Vibrator series


电动震动器
Electric vibrator

●供电：单相 AC 220V 110V，三相 AC380V
●噪音：噪音低于40分贝

●Power supply: single-phase AC 220V 110V, three-phase AC380V
●Noise: The noise is less than 40 decibels



气动震动器
Pneumatic vibrator

●气源压力：1bar~7bar
●噪音：随着压力变化噪音会增加

●Air source pressure: 1bar~7bar
●Noise: As the pressure changes, the noise will increase

气源控制系列
Air source control series


侧面安装电磁阀(NAMUR标准)
Side-mounted solenoid valve(NAMUR standard)


接管电磁阀
Take over solenoid valve


气源减压阀
Air source pressure reducing valve

●电磁阀
●供电：DC 24V；　AC 220V 110V
●压力：≤8bar
●防护：IP65/IP69
●防爆：1. 本安防爆等级Ex ia II Bt4；2.隔爆等级 EXD II BT4

●Solenoid valve
●Power supply: DC 24V; AC 220V 110V
●Pressure: ≤8bar
●Protection: IP65/IP69
●Explosion-proof: 1.Current explosion-proof grade Ex ia II BT4. 2.EXD II BT4