卧式气动执行器
Horizontal pneumatic actuator



执行器角度:
0–90° ; 0–120° ; 0–180°
外壳颜色可选
功能配置可选

Actuator Angle:
0–90° ; 0–120 ° ; 0–180 °
Case color is optional
Function Configuration Optional



执行器+本安防爆定位器
Actuator + intrinsic safety explosion–proof positioner



执行器+隔爆定位器
Actuator + Ex d explosion–proof positioner

执行器+隔爆控制单元
Actuator + Ex d explosion–proof control unit





执行器+本安防爆控制单元
Actuator + intrinsic safety explosion–proof control unit

不锈钢执行器+阀门
Stainless steel actuator + Valve





执行器+隔爆反馈器+电磁阀
Actuator + flame–Ex d explosion–proof device+electromagnetic valve

电动执行器
Electric actuator



低噪音、低功耗、大扭矩、
IP68防护、功能多样、转速可选

Low noise, low power consumption,
high torque, IP68 protection, versatility,
speed optional



技术特点

- 扭矩：15N.M~2000N.M
- 电源：AC24V/110V/220V/380V; DC12V/ V24V/220V
- 运行速度：0–90° 10S,15S,20S,30S,50S
- 工作温度：–20℃ 到 +60℃
- 执行动作：旋转行程(角行程)
- 防护等级：IP68
- 防爆等级：EX DII BT4
- 功能配置：开关型、无源触点型、智能调节型、位置反馈型

Technical Features

- Torque: 15N.M~2000N.M
- Power supply: AC24V/110V/220V/380V; DC12V/V24V/220V
- Operating speed: 0–90° 10S, 15S, 20S, 30S, 50S
- Operating temperature: –20 ° C to +60 ° C
- Execution action: Rotational stroke (corner stroke)
- Protection level: IP68
- Explosion–proof grade: EX DII BT4
- Function configuration: switch type, passive contact type, intelligent adjustment type, position feedback type

迷你型电动执行器
Mini electric actuator



扭矩Torque≤20NM，输出Output 90°



电动蝶阀
Electric butterfly valve