球阀
Ball valve

QF-DX Series

蝶式球阀
Butterfly type ball valve

小扭矩，使用寿命长、全脱脂、密封弹性补偿、体积小、内部有滞留、外观有死角、非常灵活功能组合、无需专业工具即可维护、经济、简单、可靠。

Small torque, long service life, full degreasing, sealing elastic compensation, small size, internal retention, dead spots in appearance, very flexible function combination, maintenance without professional tools, economical, simple and reliable.





Size: 1"–4", DN25–DN100

蝶式球阀与标准球阀相比较具有更小体积、更少滞留、
可配置CIP/SIP清洗和杀菌接口。

Compared to standard ball valves, butterfly type ball valves offer smaller volume, less retention, and can be configured with CIP/SIP cleaning and sterilization interfaces.



CIP inlet

CIP outlet



蝶式球阀可适配于卧式、立式、电动等各种执行器。
也可适配各种控制器，如控制单元、定位器、反馈器等。

Butterfly ball valve can be adapted to various actuators such as horizontal, vertical and electric. It can also be adapted to various controllers, such as control units, positioners, feedback, etc.



QF-3T-23 Series

三通球阀
Three way ball valve

2023款三通球阀是我们精心设计的一款产品，它具有更小的滞留、更小体积、更高承压、更加明确开启位置指示、更小的扭矩、更加美观等技术特点。

2023 3–way ball valves are well–designed, which has technical characteristics such as smaller retention, smaller volume, higher pressure, clearer opening position indication, less torque, and more aesthetics.



技术特点
Technical Features


规格：1"–4", DN25–DN100
材质：SS304, SS316L
温度：–20℃到130℃
压力：真空–10bar

Size: 1"–4", DN25–DN100
Material: SS304, SS316L
Temperature: –20° C to 130° C
Pressure: vacuum – 10 bar




通过指示确认阀门位置
Confirm valve position with instructions


T型三通球阀工作示意图
Working diagram of T-type three-way ball valve




0° A 与 B、C相通Interconnect



左旋Left–handed 90° A与B相通Interconnect




右旋Right–handed 90° A 与 C相通Interconnect




180° B 与 C相通Interconnect

L型三通球阀工作示意图
Working diagram of L-type three-way ball valve



右旋Right–handed 90° A 与 B相通Interconnect



左旋Left–handed 90° A与C相通Interconnect