

DJ-AK-PQG type

杠杆式排气阀
Lever type exhaust valve

SIZE: DN25–DN100; 1"–4"
排气压力Exhaust pressure: 0.5–3bar
工作温度Working temperature: 130℃
密封Sealing: EPDM、FKM
材质Material: 304/1.4301; 316L/1.4404



DJ-AK-GZK type

杠杆式防止真空阀
Lever type anti-vacuum valve

SIZE: DN25–DN100; 1"–4"
真空压力Vacuum pressure: –0.5 到–0.9bar
工作温度Working temperature: 130℃
密封Sealing: EPDM、FKM
材质Material: 304/1.4301; 316L/1.4404





DJ-AK-PQF type

浮球式排气阀
Float type exhaust valve

浮球排气阀是一款利用
浮球密度＜液体的密度，而产生的排气和关闭。

The float exhaust valve is a
The float density <the density of the liquid,
while the exhaust gas is generated and closed.

SIZE: DN25–DN40; 1"–1.5"
工作压力Working pressure: 5bar
材质Material: 316L/1.4404
工作温度Working temperature: 80℃ PP; 120℃ EPDM
材质Material: 316L/1.4404



DJ-AK-HXF type


呼吸阀
Breathing valve

呼吸阀是一款可以破真空和压力过载排气的多功能阀门。
可排气、破真空、体积小、简单、经济、高效。

The breathing valve is a multifunctional valve that
can break vacuum and exhaust pressure from overload.
Can exhaust, break vacuum, small size, simple,
economical and efficient.

SIZE: DN25–DN100; 1"–4"
真空压力Vacuum pressure: –0.5 到–0.9bar
排气压力Exhaust pressure: 0.5–2bar
工作温度Working temperature: 130℃
密封Sealing: EPDM、FKM、Silicon
材质Material: 304/1.4301; 316L/1.4404





容器大于设定压力，阀门开启排气
安全排泄
Container greater than the set pressure,
valve open exhaust, Safe discharge



容器产生负压，阀门开启吸气
防止真空
The container creates negative pressure,
Valve opening suction, Vacuum protection