取样阀
Sampling valve

无滞留取样阀
No retention sampling valve

阀体材质：316L/PEEK　密封材质：PTFE　Body material: 316L/PEEK　Sealing material: PTFE

DJ-QY-WZL type

1、偏心安装接口　1. Eccentric installation interface
2、中心安装接口　2. Center installation interface



取样阀
Sampling valve

接口方式：焊接、螺纹、卡箍、螺母 Connection way: welded, threaded, clamped, nut

DJ-QY type

DJ-QY-Z 直通取样阀
DJ-QY-Y Y型取样阀
DJ-SY-SN 酸奶取样阀


DJ-QY-Z Straight way sampling valve
DJ-QY-Y Y type sampling valve
DJ-SY-SN Yogurt Sampling Valve



DJ-QY-Z　DJ-QY-L　DJ-QY-Y　DJ-QY-Y　DJ-QY-SN

液位阀
Liquid level valve

接口方式：焊接、螺纹、卡箍、螺母 Connection way: welded, threaded, clamped, nut



DJ-QY-YW-A 液位阀 A
DJ-QY-YW-B 液位阀-B
DJ-QY-YW-C 液位阀-C

DJ-QY-YW-A Liquid level valve A
DJ-QY-YW-B Liquid level valve-B
DJ-QY-YW-C Liquid level valve-C



DJ-QY-YW-A　DJ-QY-YW-B　DJ-QY-YW-C

清洗技术
Cleaning technology



DJ-QX-type

清洗技术系列产品其包含，360° 清洗器、旋转清洗球阀、固定清洗球、罐底管道清洗阀。

The cleaning technology series products include 360° cleaning device, rotating cleaning ball valve, fixed cleaning ball, tank bottom pipeline cleaning valve.

360°清洗器
360° Cleaning device

DJ-QX-PS type



360° 无死角清洗、低液损耗、自润滑、自清洗、清洗距离可达22M。

360° no dead angle cleaning, low fluid loss, self-lubricating, self-cleaning, cleaning distance up to 22M.

该清洗器主要用来清洗较为顽固污渍和≤22米直径容器罐体设备，和其他清洗设备相比较有着非常大的技术优势，如更少的流量、更短的时间、360° 全覆盖清洗、无死角、自润滑、清洗更加洁净等技术特点。

This cleaning device is mainly used to clean more stubborn stains and ≤22m diameter container and tank equipment. Compared with other cleaning equipment, it has very large technical advantages, such as less flow, shorter time, 360° full coverage cleaning, No dead angles, self-lubricating, cleaner cleaning and other technical characteristics.