人孔
Manhole

阻尼慢开式人孔
Damping open-slowly manhole

它安装有阻尼系统，当打开或关闭盖子时则通过设定阻尼速度关闭或开启。
With damping system, when open or close the manhole, the speed is adjustable.



圆形常压人孔
Round normal pressure manhole

DJ-RK-Yx type

规格 Size: 102/152/200/250/300/350/450/500/550/600/700/800
密封材质 Seal material: EPDM; FKM; Silcon; HNBR
壳体材质 Shell material: 304/1.4301; 316L/1.4404
手轮材质 Handwheel material: 尼龙Nylon、304
工作温度 Operating temperature: –20℃~130℃
工作压力 Working pressure: ≤0.5bar



圆形压力人孔
Round pressure manhole

DJ-RK-YL type

规格 Size: 102/152/200/250/300/350/450/500/550/600/700/800
密封材质 Seal material: EPDM; FKM; Silcon; HNBR
壳体材质 Shell material: 304/1.4301; 316L/1.4404
手轮材质 Handwheel material: 尼龙Nylon、304
工作温度 Operating temperature : –20℃~130℃
工作压力: 推荐4bar，最大压力10bar 可根据用户实际需要
Working pressure: Recommended 4 bar, max pressure 10 bar. According to the actual needs of users



方形人孔
Square manhole

DJ-RK-FX-MINI type

规格 Size: 120*180, 185*235, 200*280
密封材质 Seal material: EPDM; FKM; Silcon; HNBR
壳体材质 Shell material: 304/1.4301; 316L/1.4404
手轮材质 Handwheel material: 尼龙Nylon、304
工作温度 Operating temperature: –20℃~130℃
工作压力 Working pressure: ≤0.5bar

