仪表
Meter



- 变送器：温度、压力、液位、流量、Pt100、等各种变送器
- 开关：隔膜压力表、压力开关、液位开关、温度开关
- 传感器：电感传感器、防爆电感传感器、PNP NPN
- 电磁阀：贴板式、接管式
- 气源附件：气源过滤减压阀
- 防护等级：IP69 IP65
- 防爆等级：可根据用户定义
- 电源：DC 24V AC220V AC110V
- 输出信号：4–20mA，0–5V，0–10V
- 材质：316L/304

东正选用的仪表产品都具有高洁净的等级且都为国内或国际一线品牌如SMC、FESTO、P+F、ANDERSON–NEGELE、LABOM、AirTAC等各种优质的合作伙伴。

The instrument products selected by DONJOY all have high grade of cleanliness and are all domestic or international top brands,such as SMC,FESTO,P+F,ANDERSON–NEGELE,LABOM,AirTac etc various high–quality partners.

- Transmitter: Temperature, pressure, liquid level, flow, Pt100 etc
- Switch: diaphragm pressure gauge, pressure switch, liquid level switch, temperature switch
- Sensor: inductive sensor, explosion–proof inductive sensor, PNP NPN
- Solenoid valve: namur–mount, tracheal connection type
- Air source accessories: air source filter pressure reducing valve
- Protection level: IP69 IP65
- Explosion–proof grade: can be defined according to users
- Power supply: DC 24V AC220V AC110V
- Output signal: 4–20mA, 0–5V, 0–10V
- Material: 316L/304

压力与液位变送器-系列 Pressure and level transmitters - Series

DJ YL 10 mA 06 TC1 DJ

- 品牌：安德森耐格(NG)；蓝博(LB)；东正定制(DJ)
  Brand: Anderson Naig (NG); Rambo (LB); Dongzheng Custom (DJ)
- 卡箍25.4(TC0.5) 卡箍 50.5(TC1) 卡箍64(TC2) 锥螺纹(RC1/2) 直螺纹(G1/2)
  Clamp 25.4(TC0.5) Clamp 50.5(TC1) Clamp 64(TC2) Cone thread (RC1/2) Straight thread (G1/2)
- 材质：304(04)316L(06)
  Material: 304(04)316L(06)
- 信号类似：IO–link(IO)；4–20mA(mA)
  The signal is similar: IO–link (IO); 4–20mA(mA)
- 压力等级：10bar(10) 6bar(6) 3bar(3) 1bar(1)
  Pressure rating: 10bar(10) 6bar(6) 3bar(3) 1bar(1)
- 类别：压力变送器(YL) 液位变送器(YW) 液位开关(YK)
  Category: Pressure Transmitter(YL) Level Transmitter(YW) Level Switch(YK)

压力变送器系列
Pressure transmitter series



压力变送器
Pressure transmitter

- 材质：304/1.4301，316L/1.4404
- 压力：0.5.....30bar(根据用户需求)
- 温度：–30℃~150℃
- 模拟量输出：4–20mA，0–5V，0–10V
- 开关量输出：PNP NPN
- 供电：DC 24V
- 防护：IP65/IP69



数字显示–压力变送器
Digital display–pressure transmitter

- Material: 304/1.4301, 316L/1.4404
- Pressure: 0.5.....30bar (according to user requirements)
- Temperature: –30℃~150℃
- Analog output: 4–20mA, 0–5V, 0–10V
- Switch output: PNP NPN
- Power supply: DC 24V
- Protection: IP65/IP69

液位变送器系列
Liquid level transmitter series



液位变送器/液位开关
Liquid level transmitter /Liquid level switch

- 材质：304/1.4301，316L/1.4404
- 液位：根据用户实际需求
- 温度：–30℃~150℃
- 模拟量输出：4–20mA，0–5V，0–10V
- 开关量输出：PNP NPN
- 压力：10bar(适用于真空环境)
- 供电：DC 24V
- 防护：IP65/IP69

- Material: 304/1.4301, 316L/1.4404
- Liquid level: According to the actual needs of users
- Temperature: –30℃~150℃
- Analog output: 4–20mA, 0–5V, 0–10V
- Switch output: PNP NPN
- Pressure: 10bar (suitable for vacuum environment)
- Power supply: DC 24V
- Protection: IP65/IP69