温度变送器系列
Temperature transmitter series



- ●材质：304/1.4301，316L/1.4404
- ●探头：长度可根据用户需求定义
- ●温度：可根据用户需求定义如150℃
- ●模拟量输出：4–20mA，PT100
- ●开关量输出：PNP NPN
- ●压力：10bar(适用于真空环境)
- ●供电：DC 24V
- ●防护：IP65/IP69

- ●Material: 304/1.4301, 316L/1.4404
- ●Probe: length can be defined according to user needs
- ●Temperature: can be defined as 150℃ according to user requirements
- ●Analog output: 4–20mA, Pt100
- ●Switch output: PNP NPN
- ●Pressure: 10bar (suitable for vacuum environment)
- ●Power supply: DC 24V
- ●Protection: IP65/IP69

温度变送器-系列 Temperature Transmitter - Series

DJ WBS 150 010 mA 04 TC1 DJ

- 品牌：安德森耐格(NG); 蓝博(LB); 东正定制(DJ)
  Brand: Anderson Naig (NG); Rambo (LB); Dongzheng Custom (DJ)
- 卡箍25.4(TC0.5) 卡箍 50.5(TC1) 卡箍64(TC2) 锥螺纹(RC1/2) 直螺纹(G1/2)
  Clamp 25.4 (TC0.5) Clamp 50.5 (TC1) Clamp 64 (TC2) Cone thread (RC1/2) Straight thread (G1/2)
- 材质Material：304(04) 316L(06)
- 信号类似：IO–link(IO); 4–20mA(mA); PT100/1000(PT)
  The signal is similar: IO–link (IO); 4–20mA(mA); PT100/1000(PT)
- 探杆长度：5mm(005); 10mm(010); 20mm(020); 50mm(050); 100mm(100)
  Probe length: 5mm (005); 10mm(010); 20mm(020); 50mm(050); 100mm(100)
- 温度等级：150℃(150); 200℃(200); 250℃(250)
  Temperature grade: 150° C (150); 200℃(200); 250℃(250)
- 类别：温度变送器(WBS); PT100(Pt100) PT1000(Pt1000) PT200(Pt200)
  Category: Temperature transmitter (WBS); PT100(Pt100) PT1000(Pt1000) PT200(Pt200)

音叉物位传感器
Tuning fork level sensor



- ●环境温度：80℃
- ●模拟量输出：4–20mA，0–5V，0–10V
- ●开关量输出：PNP NPN
- ●供电：DC 24V AC220V/110V
- ●防护：IP65/IP69

- ●Environmental temperature: 80℃
- ●Analog output: 4–20mA, 0–5V, 0–10V
- ●Switch output: PNP NPN
- ●Power supply: DC 24V AC220V/110V
- ●Protection: IP65/IP69

流量变送器系列
Flow transmitter series



- ●材质：304/1.4301，316L/1.4404
- ●流量：根据用户定义
- ●温度：–30℃~150℃ (根据用户定义)
- ●模拟量输出：4–20mA，0–5V，0–10V
- ●开关量输出：PNP NPN
- ●压力：10bar(适用于真空环境)
- ●供电：DC 24V
- ●防护：IP65/IP69
- ●防爆：1. 本安防爆等级Ex ia Ⅱ Bt4；2.隔爆等级 EXD Ⅱ BT4

- ●Material: 304/1.4301, 316L/1.4404
- ●Flow: According to user definition
- ●Temperature: –30℃~150℃ (according to user definition)
- ●Analog output: 4–20mA, 0–5V, 0–10V
- ●Switch output: PNP NPN
- ●Pressure: 10bar (suitable for vacuum environment)
- ●Power supply: DC 24V
- ●Protection: IP65/IP69
- ●Explosion–proof: 1.Intrinsically–safe explosion–proof Ex ia Ⅱ BT4. 2.EXD Ⅱ BT4

流量变送器-系列 Flow Transmitter - Series

DJ DLB 2.0 150 mA PTFE 04 TC

- 连接方式：法兰(F); 卡箍(TC)
  Connection mode: flange (F); Clamp (TC)
- 壳体材质：304(04); 316L(06); 铸铁(WB)
  Shell material: 304 (04); 316L(06); Cast Iron (WB)
- 内衬材质：PTFE(PTFE); FPA(FPA)
  Lining material: PTFE (PTFE); FPA(FPA)
- 信号类似：IO–link(IO); MOD BUS RS485(RS); 4–20mA(mA)
  The signal is similar: IO–link (IO); MOD BUS RS485(RS); 4–20mA(mA)
- 温度等级：150℃(150); 200℃(200)；250℃(250)
  Temperature grade: 150° C (150); 200℃(200)； 250℃(250)
- 规格：1"(1.0); 1.5"(1.5); 2"(2.0); 2.5"(2.5); 3"(3.0); 4"(4.0)
  Size:1"(1.0); 1.5"(1.5); 2"(2.0); 2.5"(2.5); 3"(3.0); 4"(4.0)
- 类别：电磁流量变送器(DLB)涡街流量变送器(WLB)
  Category: Electromagnetic Flow Transmitter (DLB) Vortex Flow Transmitter (WLB)